

FOSHAN PINSHANG MACHINERY CO., LTD

<https://en.fspinshang.com> pinshangflexo@gmail.com whatsapp: +86 13791266555

printer slotter for corrugated boxes

Automatic Flexo Printer Slotter Die Cutter

Gearbox 4 shafts automatic lead edge feeder.

Flexo printer cylinder and slotter shaft phases adjusted by servo motors.

Printing units are equipped vacuum transfer.

Eight shafts slotter design, pre-creaser first, creaser second, creaser third, slotter.

Inverter motor speed compensation system from die cutter unit.

PLC remote control system, can manager and check through internet.

9000 order memory system with computer operation system.



Model	PS-Y6-0920	PS-Y6-0924
Max machine speed	250pcs/min	250pcs/min
Max feeding size	2100*880mm	2500*880mm
Max skip feeding size	2100*1100mm	2500*1100mm
Min feeding size	680*280mm	680*280mm
Max printing size	2000*850mm	2400*850mm
Max die cutting size	2400*850mm	2400*850mm
Standard printing plate	7.2mm	7.2mm
Min slotting distance	245*75*245*75mm	245*75*245*75mm
Max slotting depth	250mm	250mm
Paper board thickness	1.5-12mm	1.5-12mm
Voltage supply	380V, 50HZ, 3Phase	380V, 50HZ, 3Phase

Model	PS-Y6-1224	PS-Y6-1228
Max machine speed	200pcs/min	180pcs/min
Max feeding size	2500*1180mm	2900*1180mm
Max skip feeding size	2500*1400mm	2900*1400mm
Min feeding size	700*350mm	700*350mm

FOSHAN PINSHANG MACHINERY CO., LTD

<https://en.fspinshang.com> pinshangflexo@gmail.com whatsapp: +86 13791266555

Max printing size	2400*1150mm	2800*1150mm
Max die cutting size	2400*1150mm	2800*1150mm
Standard printing plate	7.2mm	7.2mm
Min slotting distance	260*75*260*75mm	260*75*260*75mm
Max slotting depth	300mm	300mm
Paper board thickness	1.5-12mm	1.5-12mm
Voltage supply	380V, 50HZ, 3Phase	380V, 50HZ, 3Phase

Model	PS-Y6-1424	PS-Y6-1428
Max machine speed	180pcs/min	170pcs/min
Max feeding size	2500*1420mm	2900*1420mm
Max skip feeding size	2500*1600mm	2900*1600mm
Min feeding size	700*380mm	700*380mm
Max printing size	2400*1390mm	2800*1390mm
Max die cutting size	2400*1390mm	2800*1390mm
Standard printing plate	7.2mm	7.2mm
Min slotting distance	260*75*260*75mm	260*75*260*75mm
Max slotting depth	350mm	350mm
Paper board thickness	1.5-12mm	1.5-12mm
Voltage supply	380V, 50HZ, 3Phase	380V, 50HZ, 3Phase

Model	PS-Y6-1628	PS-Y6-1632
Max machine speed	150pcs/min	140pcs/min
Max feeding size	2900*1580mm	3300*1580mm
Max skip feeding size	2900*1800mm	3300*1800mm
Min feeding size	700*420mm	800*420mm
Max printing size	2800*1550mm	3200*1550mm
Max die cutting size	2800*1550mm	3200*1550mm
Standard printing plate	7.2mm	7.2mm
Min slotting distance	275*80*275*80mm	275*80*275*80mm
Max slotting depth	400mm	400mm
Paper board thickness	1.5-12mm	1.5-12mm
Voltage supply	380V, 50HZ, 3Phase	380V, 50HZ, 3Phase

[printer slotter for corrugated boxes](#)

<https://www.youtube.com/watch?v=RiruDt8dbYg>